

Application Guidelines

SHEETROCK® Brand Joint Compounds and Finishes

The following guidelines for USG Sheetrock® Brand interior finishing products are to assist the contractor with the most appropriate system to join and finish plasterboard surfaces

		Joint I	Joint Tape Type			
	Sheetrock [®]	Paper	Fiberglass #			
Best	Easy Sand™ - Setting Type	✓	1			
	Durabond [®] - Setting Type	✓	/			
	Taping - Ready Mixed	✓	Do not use			
Good	Total™ - Ready Mixed	✓	Do not use			
	# NOTE: Use only USG Sheetrock [®] Brand Fibrec Tape for full system Warranty					
Best	Easy Sand - Setting Type					
	Durabond - Setting Type					
Good	Total - Ready Mixed					
	Total Lite™ - Ready Mixed					
	Plus 3 [™] - Lightweight Ready Mixed					
	Topping - Ready Mixed					
	Taping - Ready Mixed					
	Hand or Pole Sanding Machine San					
Best	Plus 3 - Lightweight Ready Mixed Total - Ready Mixed					
	Total Lite - Ready Mixed					
	Topping - Ready Mixed					
Good	Total - Ready Mixed	eady Mixed				
Best	Spray Skim	<u> </u>				
Good	Total - Ready Mixed					
adda	Total Troady Mixed					
Best	Tuff-Hide [®]					
	Good Best Good Best Good	Best Easy Sand™ - Setting Type Durabond® - Setting Type Taping - Ready Mixed # NOTE: # NOTE: Best Easy Sand - Setting Type Durabond - Setting Type Durabond - Setting Type Good Total - Ready Mixed Total Lite™ - Ready Mixed Plus 3™ - Lightweight Ready Mixed Topping - Ready Mixed Taping - Ready Mixed Hand or Pole Sanding Plus 3 - Lightweight Ready Mixed Total Lite - Ready Mixed Total Lite - Ready Mixed Total Lite - Ready Mixed Total - Ready Mixed Total - Ready Mixed Good Total - Ready Mixed Best Spray Skim Good Total - Ready Mixed	Sheetrock® Paper Best Easy Sand™ - Setting Type Durabond® - Setting Type Taping - Ready Mixed # NOTE: Use only USG Sheetrock® Tape for full system Warra Best Easy Sand - Setting Type Durabond - Setting Type Good Total - Ready Mixed Total Lite™ - Ready Mixed Plus 3™ - Lightweight Ready Mixed Topping - Ready Mixed Taping - Ready Mixed Taping - Ready Mixed Total Lite - Ready Mixed Total - Ready Mixed			

Application Guidelines

SHEETROCK® Brand Joint Compounds and Finishes

SRAG/6-06

Sheetrock [®]	Taping	Filling	Finishing	Skimming	Level 5	Ease of Sanding	Low Shrinkage	Cornice Adhesive
Durabond	11	11					11	11
Easy Sand	11	11				11	11	
Taping	11	1						
Topping		1	11			11	11	
Total	1	1	1	1		/	1	
Total Lite	AT.	1	11			11	11	
Plus 3	V	1	11			//	11	
Spray Skim				11		✓	N/A	
Tuff-Hide					11	N/A	N/A	



email: info-anz@usgi.co.nz

www.usg.com/australasia